
Specifications

Phenolic Partitions Floor Anchored/Overhead Braced 6.3

Phenolic Partitions with Floor Anchored/Overhead Braced Mounting Style

Part 1 - General

1.01 Work Included

A. The toilet partitions shall be phenolic material with floor anchored overhead braced mounting style as manufactured by **ASI Accurate Partitions**, Burr Ridge, Illinois.

B. Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of partitions.

Part 2 – Product

2.01 Doors and Pilasters – Shall be ¾” thick with solid phenolic core and decorative surface sheet on both faces.

2.02 Panels and Urinal Screens – Shall be ½” thick with solid phenolic core and decorative surface sheet on both faces.

2.03 Material – Doors, panels, pilasters and urinal screens shall be fabricated from phenolic material comprised of multiple layers of melamine resin impregnated kraft paper, and a decorative surface sheet on both faces. All layers shall be fused together under high temperature and pressure.

2.04 Finish – All components shall be water-resistant. Rough edges shall be machine sanded with a 45 degree radius edge.

2.05 Color - Shall be selected from **Accurate's** full range of standard designer colors.

2.06 Door Hardware – Shall be **Accurate**, gravity cam-action hinge that permits door to return to a pre-set position when not locked. Hinge, strike/keeper and slide latch shall be brushed finish to resist corrosion and thru-bolted with tamper resistant barrel nuts and shoulder screws. Cam-action hinge shall allow emergency access by lifting the door from the bottom.

2.07 Mounting Hardware – Cast stainless steel stirrup brackets with brushed finish shall be secured to walls and pilasters with stainless steel tamper resistant fasteners. Panels shall be thru-bolted with tamper resistant barrel nuts and shoulder screws.

2.08 Construction Design – Partitions shall be floor anchored with a 3/8” x 1” mounting bar attached to the bottom of the pilaster. Each mounting bar shall be anchored to the floor with 3/8” wedge anchors. The anchoring system shall be concealed by a type 304 stainless steel trim shoe with a #4 finish. Aluminum headrail with anti-grip profile shall provide overhead bracing and span all partitions and brace the end pilaster to the back wall.

Part 3 – Execution

3.01 Installation – Shall be installed in accordance to the **Accurate** installation instructions with partitions rigid, straight and plumb. Doors and panels shall be mounted 12” above the finished floor.

3.02 Warranty – **ASI Accurate Partitions** guarantees its phenolic partitions, properly maintained, against delamination, breakage or corrosion for 10 YEARS from the date of receipt by the customer. If material is found defective during that period, the material shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.