

Specifications

Color-Thru Phenolic Shower Dividers and Dressing Compartments 7.7CT

Color-Thru Phenolic Shower Dividers and Dressing Compartments

Part 1 - General

1.01 Work Included

A. The shower dividers and dressing compartments shall be phenolic material with floor anchored/overhead braced mounting style as manufactured by **ASI Accurate Partitions**, Burr Ridge, Illinois.

B. Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

1.02 Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of stalls and compartments.

Part 2 – Product

2.01 Panels – Shall be ½ " thick solid phenolic core and decorative surface sheet on both faces. Phenolic core shall be the same color as the decorative surface sheets.

2.02 Pilasters – Shall be ¾ " thick solid phenolic core and decorative surface sheet on both faces. Phenolic core shall be the same color as the decorative surface sheets.

2.03 Material – Panels and pilasters shall be fabricated from phenolic material comprised of multiple layers of melamine resin impregnated kraft paper, and a decorative surface sheet on both faces. All layers shall be fused together under high temperature and pressure.

2.04 Finish – All components shall be water-resistant. Rough edges shall be machine sanded with a 45 degree radius edge and black core.

2.05 Color - Shall be selected from **ASI Accurate's** full range of color-thru colors.

2.06 Shower Divider Construction Design – Shall be floor anchored/overhead braced. Panels and pilasters attached to walls with standard hardware and anti-grip extruded aluminum headrail. Anti-grip extruded aluminum headrail incorporates channel for shower curtain hooks.

2.07 Dressing Compartment Construction Design - Shall be floor anchored/overhead braced and may be attached to the shower stalls. Panels and pilasters attached to shower stall with standard hardware and anti-grip extruded aluminum headrail. Dressing compartment may be supplied with curtain or door.

Part 3 – Execution

3.01 Installation – Shall be installed in accordance to the **ASI Accurate** installation instructions with compartments rigid, straight and plumb.

3.02 Warranty – **ASI Accurate Partitions** guarantees its phenolic partitions, properly maintained, against delamination, breakage or corrosion for 25 YEARS from the date of receipt by the customer. If material is found defective during that period, the material shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.